



**NORTECH**  
TRAFFIC

# TD280

## Dual Channel Detector

The 8 series, Nortech’s new flagship Vehicle Detector range addresses the market’s need for a slimline, advanced vehicle detection solution. The powerful architecture facilitates on-board vehicle classification including speed, vehicle length and headway. The relay and opto outputs are fully configurable, allowing for alarms and alerts on desired events.

Nortech’s Automatic Frequency Selection (AFS) algorithms have been refined and optimised resulting in simplified setup and installation of complex multi-lane traffic sites. The new wireless diagnostic unit, the DU800 allows for detector configuration and installation feedback on any iOS or Android device. This eliminates the need to adjust any mechanical interfaces once the unit has been installed. The DU800 also allows for vehicle profile streaming.

The new slimline, DIN Rail mount housing allows for more physical connections than the traditional relay base and Nortech’s innovative modular design allows for the expansion of detection solutions, including: output expansion units, channel expansion units, and communications interfaces.

The 8 series detectors simply work, offering peace of mind in even the most complex installation. They are available in both single and dual channel with either relay or opto outputs.

### APPLICATIONS

- Traffic Control Applications
- Tolling Equipment
- Traffic Analysis



### SPECIFIC FEATURES

<b>Slimline Form Factor</b>	The TD280 is the slimmest of the Nortech boxed traffic detectors facilitating installation in even the most physically constrained environments.
<b>Expandable</b>	The innovative expansion port on the TD280 allows for the addition of modules to the system. These modules include but are not limited to extra outputs, extra detection channels and communication modules.
<b>AFS</b>	Automatic Frequency Selection (AFS) automatically examines the detector environment and sets the optimal operating frequency to ensure minimal interference and maximum reliability, significantly decreasing installation time. Frequency can also be manually set via wireless configuration channel.
<b>PowerFail Memory</b>	In the event of a power failure, the TD280 will retain the presence of the vehicle when power is restored. The TD280 is also able to determine if a vehicle has driven onto the loop while the power is off, and detect it immediately when the power returns. This is most useful in applications where damage to vehicles could occur (E.g. Rising Bollards). The PowerFail memory is infinite.
<b>Diagnostics</b>	Comprehensive, wireless diagnostics allow for accurate diagnosis of loop and installation problems as well as configuration adjustments to eliminate issues. This is made possible via Nortech’s DU800 and Integr8 App

## TECHNICAL DATA

<b>Self-tuning Range</b>	20 $\mu$ H to 1000 $\mu$ H
<b>Sensitivity</b>	Ranging from 0.01% $\Delta$ L/L to 5% $\Delta$ L/L Automatic Sensitivity Boost (ASB) is selectable per channel
<b>Frequency</b>	Automatic Frequency Selection (AFS) or select from 6 frequency bands 30 - 150kHz (Frequency is determined by loop geometry)
<b>Automatic Frequency Selection</b>	Automatically evaluates all frequency bands on startup and selects the most suitable in the given environment based on signal strength and noise.
<b>Presence Time</b>	Permanent or limited selectable per channel
<b>Drift Compensation</b>	Incorporated method of tracking changes caused by environmental conditions at a rate approximating 1% $\Delta$ L/L per minute
<b>Anti-locking</b>	Incorporated algorithm accommodates the influence of positive inductance changes to avoid detector lock-up
<b>Relay Outputs</b>	2 programmable relays with NO, NC and COM connections exposed. Options for presence or pulse, pulse on detect, undetect or fault and each relay has configurable Filter, Delay and Extend options. Relays also configurable for alerts on classification events
<b>Relay Mode</b>	Relays can be configured to operate as Fail Safe or Fail Secure with the ability to actuate on a Fault condition in Fail Safe mode
<b>Opto Outputs</b>	3 Opto outputs provided as an alternative to relays. Each is individually configurable and may be associated with any channel or alert
<b>Protection</b>	Polarity protection, loop isolation transformer, zener diode clamping, gas discharge tubes, 50-60Hz Noise Rejection
<b>Power</b>	12 - 24V $\pm$ 10% (AC/DC ) 90V - 230V $\pm$ 10% AC 50/60Hz
<b>Connections</b>	DIN Rail mount 3 x 3 Way Connectors and 1 x 4 Way connector
<b>Operating Temperature</b>	-40°C to +80°C
<b>Dimensions</b>	Maximum outer dimensions are 94mm x 94mm x 22,5mm.

## ORDERING INFORMATION

<b>308FT4201</b>	TD282 Dual Channel 90 - 230V AC
<b>308FT4202</b>	TD284 Dual Channel 12 -24V AC/DC
<b>308FT4203</b>	TD282 Dual Channel 90 - 230V AC Opto Outputs
<b>308FT4204</b>	TD284 Dual Channel 9 - 24V AC/DC Opto Outputs